




Thank you for purchasing the 9XX Dashboard speaker fitting kit for the Porsche 996 & 986 (Boxster).

Fitting of the kit is simplicity itself, but we have included this brief fitting guide.

**Contents of kit.**

1. Alpine speaker adapter ring. (2 Included)
2. Single point fixing (2 included)
3. Two point fixing (2 included)
4. Wiring adapter (2 Included)
5. This instruction page
6. Tips and tricks page.



**1. Removing your original speakers.**

Your speakers are held into the dashboard or rear of the car with two screws, in some cars these are Philips screws, in others they can be held in place with two Torx screws.

To remove the speakers, simply remove these two screws, lift the grill and speaker assembly and disconnect the speaker wiring multi plug.

**2. Preparing your speaker grills.**

Now you have removed the speaker assembly from your car, you need to remove the old speaker. The speaker will be held in place with 3

small philips screws highlighted in this image.



If your car is fitted with a tweeter as well as the main speaker, you will need to cut the wires to it, or remove the tweeter with the main speaker. If you remove the tweeter we recommend you make the grill aperture air-tight using adhesive tape.

**3. Assembling the kit to the grills.**

Attach one of the speaker rings to your 9XX approved speaker. On some models this may require some effort and can be a tight fit. We recommend that you follow the advice in our tips sheet for advice.



Place the speaker into the grill, lining up the notch on the ring with the raised flat upright of the grill as seen in this picture.



Attach a single point fixing to the grill, clamping the speaker and ring to the grill. this fixing has a recess in one side that the grills fixing point will locate into. Re-install original screw that was located in this location



Attach two point fixing adapter in the same way as for the single point fixing.



Attach the wiring adapter as shown in this image. the adapter will only connect to your speaker in one orientation.



**4. You are now ready to re-install the grills into the dashboard.**

Connect the square end of the wiring adapter to the cars original connector.

place the grill and speaker assembly back into the dashboard. if you experience problems, please check the tips and tricks page.

**This kit is authorised for use with Alpine SXE-1025S, SPE-10C2 and SPG-10C2 Speakers.**

**THIS KIT ALSO FITS 996 REAR**